



icmr NITVAR
INDIAN COUNCIL OF
MEDICAL RESEARCH NATIONAL INSTITUTE OF TRANSLATIONAL
VIROLOGY AND AIDS RESEARCH

आई सी एम आर - राष्ट्रीय ट्रांसलेशनल वाइरॉलॉजी एवं एड्स अनुसंधान संस्थान,
(भारतीय आणुवैज्ञान अनुसंधान परिषद)
स्वास्थ्य एवं परिवार कल्याण मंत्रालय, भारत सरकार

ICMR – National Institute of Translational Virology and AIDS Research,
(Indian Council of Medical Research)
Ministry of Health and Family Welfare, Government of India

Quotation Enquiry

PP No: 0003/NITVAR-Purchase/2025-26

Date: 04/07/2025

Sales Quotations are invited on behalf of the Director, ICMR-NITVAR, Pune for the following item for the mentioned quantities along with the company profile and other documents and details asked below.

Sr No:	Item	Specifications
1	Accessibility Ramp Construction at Admin Building Entrance & Laboratory Building Entrance Length of Ramp 8.5m for both Building	As per the list attached. (Annexure I)
2	Handrail for Accessible Ramp at Admin Building and Lab Building	

All work along with required accessories has to be completed by the agency

The quotation superscribed as 'Quotation for PP No. 0003 addressed to the **Director, ICMR - National Institute of Translational Virology and AIDS Research, 73-G, MIDC, Bhosari, Pune 411026, Post Box No. 1895,** should be either dropped at the reception of ICMR-NARI, Pune or sent through by speed post /Courier latest by 29th of July, 2025 till 5:00pm in a sealed Envelop.

Documents Required to be submitted along with the quotation;


- 1 Valid Certificate of Incorporation/Registration of the Firm.
- 2 Copy of PAN and GST Registration Certificates.
- 3 Copies of at least one Purchase Order issued in each of the last three (3) Financial Years,
- 4 Valid MSME Certificate, if applicable.
- 5 Compliance Certificate affirming unconditional acceptance of all terms and conditions specified in the Enquiry Document.
- 6 Undertaking of Site Visit: A duly signed declaration on the bidder's letterhead confirming that the bidder has visited and assessed the site conditions and is fully aware of the scope of work and execution requirements.

Other Terms and Conditions:

- 1 This is an enquiry and must not be treated as order.
- 2 The ICMR-NITVAR Office reserves the right to accept or reject any or all applicant without assigning any reason
- 3 Any decision taken by the Director, ICMR NITVAR at any point of time in connection with this process shall be final and conclusive and no claim or disputes from any quarter in that regard shall be entertained.

[Signature]
04/07/25

- 4 No advance payment will be made. The payment will be made on receipt of services availed and satisfactor report of the end user.
- 5 ICMR-NITVAR Pune will not be responsible for any delay for the receipt of the quotations.
- 6 Vendors are advised to check applicable GST on their own before quoting. Buyer will not take any responsibility in this regards. GST reimbursement will be as per actuals or as per applicable rates (whichever is lower), subject to the maximum of quoted GST %.
- 7 To furnish supporting documentation in case of eligibility as an MSME.


Administrative Officer,
ICMR - NITVAR, Pune

Ramp Specifications as per NBC 2016 (Barrier-Free Design)

1. Ramp Width :Minimum clear width: 1500 mm (1.5 meters)
 2. Ramp Length: 8.5meters.
 3. Gradient (Slope) :Our gradient requirement is 1:135 (Maximum slope: 1:12
i.e., 1 unit vertical rise for every 12 units of horizontal distance).
 4. Landing :At top and bottom of ramp, of horizontal travel
 5. Landing size: Minimum 1500 mm × 1500 mm.
 6. Edge Protection :Raised curbs of minimum 50 mm height on open sides.
-

Handrail Specifications (As per IS 4963:1987 and NBC 2016)

1. Height
 - Between 800 mm to 900 mm above the ramp surface
 - Dual height handrails may be provided for children and wheelchair users
 2. Diameter and Grip
 - Circular cross-section with diameter 30–50 mm (ideal grip for hand)
 - If non-circular, the perimeter should be 100 mm to 160 mm
 3. Clearance
 - Minimum 50 mm clearance between wall and handrail
 4. Extension
 - Should extend 300 mm beyond the top and bottom of the ramp Continuity
 - Must be continuous along both sides of the ramp
 5. Surface
 - Smooth, non-slippery, and easy to grip
 - Should not rotate within its fittings
-

Surface and Finishing

- Non-slip ramp surface is mandatory
- Should be firm and stable (no loose material)

